


44 x 56 LD Stackable Pallet





SPECIFICATIONS	IN/LB	MM/KG
Length (L)	56	1,422
Width (W)	44	1,118
Height (H)	4.5	114
Overall Fork Pocket Width (W1)	32	813
Individual Fork Pocket Width (W2)	12	305
Overall Fork Pocket Length (L1)	40	1,016
Individual Fork Pocket Length (L2)	12	305
Fork Pocket Height (H1)	2.3	58
Weight	45	20
Static Load Rating	30,000	13,608
Dynamic Load Rating	1,500	680
53' Trailer Quantity	600	

DECORATION AREAS	WIDTH (IN)	HEIGHT (IN)
Brand, Barcode or RFID Area (B1)	4.0	2.0

Features & Benefits

- High-pressure injection molded plastic pallets are made from co-polymer polypropylene resin that will not absorb moisture or bacteria
- Roughened top deck reduces slippage and helps keep loads in place
- Full picture frame and cruciform bottom work smoothly with automated pallet handling equipment
- Chaffered edges around the top deck perimeter allow for more efficient distribution of strap tension on pallet and load
- Tapered bottom edges on all sides allow easy four-way entry and exit for fork lifts
- 2-piece, Snap-Lock[™] design that performs like a one-piece and without the worries of a welded pallet that can separate
- High-pressure injection molding allows Rehrig Pacific designers to strategically vary wall thickness to achieve lighter yet stronger plastic pallets when compared to other molding processes

Options

- Colors: Choice of standard or optional nonheavy metal (NHM) or FDA approved colors
- RFID compatible, works with Vision™
 Software solution

Alternative Material for Sustainability

- PCR RPC Circular Plastic Economy, Automotive Bumpers, Cart Seats
- PIR RPC Mfg Scrap

Up to 30% Black Up to 10% Color