
# **ASRS Tray**




Specifications	IN/LB	TOLERANCE (IN/LB)
Length (L)	36.17	+/- 0.10
Width (W)	21.15	+/- 0.10
Height (H)	1.74	-
Handle to Handle Length (L1)	31.19	+/- 0.10
Short Wall Flatness (F1)	0.00	+ 0.250
Long Wall Flatness (F2)	0.00	+ 0.125
Weight	7.96	+/- 0.05
53' Trailer Quantity	4,500	

Decoration Areas	WIDTH (IN)	HEIGHT (IN)
Brand Area (B1)	4.90	1.60
Barcode or Label Area (B2)	2.50	0.50







## Features & Benefits

- High-pressure injection molded using highdensity polyethylene resin for superior durability and performance
- Steel reinforcements provide support and stability by equally distributing load throughout
- Optimal footprint with ergonomic handles for manual transport and guide rails for automation tooling engagement
- Perimeter lip helps secure and protect product against damage and unnecessary replacement
- Highly nestable design saves space when empty in warehouse
- Compatible with most automated storage and retrieval systems

# Options

- Various colors available to promote brand awareness
- Molded-in logos available for customer specific branding
- RFID and barcode technology available for seamless system integration
- Separate compatible tub available for enhanced storage and versatility

**Corporate Headquarters** 4010 East 26th St., Los Angeles, CA 90058 (800) 421-6244 • (323) 262-5145

### Locations

Los Angeles, CA • Orlando, FL • Atlanta, GA • De Soto, KS Erie, PA • Dallas, TX • Kenosha, WI • Quebec, Canada Querétaro, Qro., Mexico

Web: www.rehrigpacific.com



A FAMILY TRADITION OF GROWTH, SERVICE AND INNOVATION