


## 44 x 56 High Deck Stackable Pallet





SPECIFICATIONS	IN/LB	MM/KG
Length (L)	56.0	1,422.4
Width (W)	44.0	1,117.6
Height (H)	5.13	130.18
Overall Fork Pocket Width (W1)	32.1	815.34
Individual Fork Pocket Width (W2)	12.1	307.34
Overall Fork Pocket Length (L1)	40.1	1,018.54
Individual Fork Pocket Length (L2)	12.4	314.96
Fork Pocket Height (H1)	3.5	88.9
Weight	52	23.59
Static Load Rating	30,000	13,607.85
Dynamic Load Rating	4,000	1,814.37
53' Trailer Quantity	462	

## **Features & Benefits**

- High-pressure injection molded plastic pallets are made from high density polyethylene resin that will not absorb moisture or bacteria.
- Roughened top deck reduces slippage and helps keep loads in place
- Full picture frame and cruciform bottom work smoothly with automated pallet handling equipment
- Chaffered edges around the top deck perimeter allow for more efficient distribution of strap tension on pallet and load
- Tapered bottom edges on all sides allow easy four-way entry and exit for fork lifts
- 2-piece, Snap-Lock™ design that performs like a one-piece and without the worries of a welded pallet that can separate
- High-pressure injection molding allows Rehrig Pacific designers to strategically vary wall thickness to achieve lighter yet stronger plastic pallets when compared to other molding processes

## **Options**

- Colors: Choice of standard or optional nonheavy metal (NHM) or FDA approved colors
- RFID compatible, works with Vision™
  Software solution

## Alternative Material for Sustainability

Up to 99% Black PP Up to 50% HDPE