
48x48 Standard Duty Pallet



vision.



Specifications	IN/LB	MM/KG
Length (L)	48.0	1219
Width (W)	48.0	1219
Height (H)	6.0	152
Overall Fork Pocket Width (W1)	30.1	765
Individual Fork Pocket Width (W2)	10.1	257
Overall Fork Pocket Length (L1)	30.1	765
Individual Fork Pocket Length (L2)	10.1	257
Fork Pocket Height (H1)	4.1	104
Weight	70.2	31.8
Edge Rack Capability	2,000	907
Dynamic Load Rating	4,000	1,814
Static Load Rating	30,000	4,536
53' Trailer Quantity	468	

Features & Benefits

- High-pressure injection molded using a proprietary blend of high density polyethylene and co-polymer polypropylene for superior durability, impact resistance, and performance
- Pallets do no absorb moisture or bacteria and their appearance is more attractive for retail applications than wooden pallets.
- Tapered bottom edges on all sides allow easy four-way entry and exit for pallet jacks and fork lifts.
- Full picture frame and cruciform bottom work smoothly with automated pallet handling equipment.
- Absence of any metal fasteners and splinters means no parts that can protrude and damage products or cause injury.
- Rugged and lightweight, they are easier to handle than comparable wood or other plastic pallets.
- 2-piece, Snap-Lock™ allows for quick and easy repair while reducing damage from pallet jacks thus offering substantially longer life.
- Comprehensive warranty

Options

- Available in black only
- Hot-stamped logos available for customer specific branding on all four sides
- Perimeter lip available to help secure and protect product against damage and unnecessary replacement costs
- RFID, GPS, and barcode technology available for asset tracking, visibility, and retention via Rehrig's RVision software

Corporate Headquarters

4010 East 26th St., Los Angeles, CA 90058 (800) 421-6244 • (323) 262-5145

Locations

Los Angeles, CA • Orlando, FL • Atlanta, GA • De Soto, KS Erie, PA • Dallas, TX • Kenosha, WI • Quebec, Canada Querétaro, Qro., Mexico

Web: www.rehrigpacific.com

