



40 x 48 GMA Rackable 2400 Pallet







-H1

SPECIFICATIONS	IN/LB	MM/KG
Length (L)	48	1,219.2
Width (W)	40	1,016
Height (H)	5.63	142.88
Overall Fork Pocket Width (W1)	30	762
Individual Fork Pocket Width (W2)	12.5	317.5
Overall Fork Pocket Length (L1)	33	838.20
Individual Fork Pocket Length (L2)	14	355.60
Fork Pocket Height (H1)	3.45	87.63
Weight	47	21.32
Static Load Rating	7,200	3,265.86
Dynamic Load Rating	4,200	1,905.09
2" Edge Rack Load Rating	2,400	1,088.62
53' Trailer Quantity	570	
DECORATION AREAS	WIDTH (IN)	HEIGHT (IN)
Brand, Barcode or RFID Area (B1)	4.38	2.5

Features & Benefits

- Manufactured from HDPE using high pressure injection molding creating superior strength
- Metal reinforcements provide superior edge racking capabilities and excellent impact resistance
- Deck and base components are welded for additional strength and long-term rust prevention
- Designed with large fork opening to minimize damage and provide excellent impact resistance
- Non-cruciform bottom structure reduces pallet jack damage and reduces total plastic weight
- Two-piece snap lock design allows for quick and easy repair
- Ergonomic handles eliminate dangerous and awkward pallet handling
- Molded-in top deck texture reduces case slippage

Options

- Colors: Wide variety of colors available
- Decoration: Can be hot stamped with your company's logo for added inventory control and brand awareness; Multi-color logos optional
- Optional perimeter lip available for added load stability and better alignment when stored
- FM Certification available with halogenated material
- RFID compatible, works with Vision™ Software solution

Alternative Material for Sustainability

 PCR - OCean Bound, RPC Circular Plastic Economy
PIR - RPC Mfg Scrap

Up to 30% Black Up to 10% Color

REHRIG PACIFIC COMPANY

PSS-DES-305 40 x 48 GMA Rackable 2400 Pallet_11.11.2022 © 2022 Rehrig Pacific Company. All Right Reserved.