



STD/V/DROP SPECIFICATIONS	IN/ LB	CM/ KG
Length (L)	48	1219
Width (W)	40	1016
Height (H)	46	1168
Overall Fork Pocket Width (W1)	30	762
Individual Fork Pocket Width (W2)	12	305
Overall Fork Pocket Length (L1)	32	813
Individual Fork Pocket Length (L2)	13	330
Fork Pocket Height (H1)	4	89
Folded Height (H2)	24	610
Nest Increment	12	292
Weight	102	46
Load Capacity	2000	909
Static Load Rating	7200	3273
Dynamic Load Rating	4000	1818
53' Trailer Quantity	270	

HALF HEIGHT SPECIFICATIONS	IN/ LB	CM/ KG
Length (L)	48	1219
Width (W)	40	1016
Height (H)	26	660
Overall Fork Pocket Width (W1)	30	762
Individual Fork Pocket Width (W2)	12	305
Overall Fork Pocket Length (L1)	32	813
Individual Fork Pocket Length (L2)	13	330
Fork Pocket Height (H1)	4	89
Folded Height (H2)	24	610
Nest Increment	12	292
Weight	78	35
Load Capacity	2000	909
Static Load Rating	7200	3273
Dynamic Load Rating	4000	1818
53' Trailer Quantity	270	

## Features & Benefits

- High pressure injection molding allows a lighter, yet stronger part with superior durability compared to other molding methods
- Smooth Walls with minimal to no crevices to allow for easy cleanability.
- Advanced copolymer polypropylene, with enhanced impact compared to other materials commonly in use, won't absorb moisture, harmful bacteria or pathogens
- Full picture frame and cruciform bottom supports full edge racking and ensures the pallet works smoothly with conveying and automated pallet handling equipment
- Integrally molded into the side wall, the one-piece latch eliminates costly repairs and spare parts
- Lighter weight than comparable bins, which allows for 2 additional bins per outbound shipment before "weighing out"
- Shares common industry dimensions allowing it to stack and nest with comparable plastic bins
- Bins stack securely with greater integrity, with or without the optional lid
- Walls fold down and take up less space during empty shipping and storage than comparable bins, which allows for 12% more bins per back haul

## Options

- Various Wall configurations - Standard, V Channel Opening, Drop Wall and Half Height Options
- Various Runner Configurations available.
- Various colors available
- Hot-stamped logos available for customerspecific branding
- RFID-enabled technology and barcodes available for asset tracking, visibility, and retention via Rehrig's software

DECORATION AREAS	WIDTH (IN)	HEIGHT (IN)
Branding (A)	10.25	6.25
MIL (B)	4	2.75